



# 轮式电驱剪叉平台

Wheeled electric drive scissor platform

## SJPT0607

- 整车的运输方便性、整车通过性高。  
Transport is convenient and pass through is high.
- 全高度行走，配置多重安全保护装置。  
Full height walking, equipped with multiple safety protection devices.
- 整车维修方便，日常检查及维护保养便捷。  
Daily inspection and maintenance is convenient.
- 人机交互，故障诊断，参数读写，系统监控。  
Man-machine interaction, fault diagnosis, parameter reading and writing, system monitoring.
- 新能源动力，体积小、重量轻、无污染。  
New energy power, small size, light weight, non-pollution.
- 直流电机驱动，效率高、灵敏度好。  
Dc motor drive, high efficiency, good sensitivity.



### 产品配置

#### Machine Parameters

动作蜂鸣 Action buzzer	全行程行走 Full travel	自动刹车系统 ABS
折叠围栏 Folding fence	工作时间表 Working hours table	紧急停止按钮 Emergency button
免维护电池 Maintenance-free battery	工作频闪灯 Working strobe light	故障诊断系统 Fault diagnosis system
安全检修支撑 Safety maintenance support	平台自锁门 Self-locking door	倾斜保护系统 Tilt protection system
标准运输叉车孔 Standard transport forklift hole	紧急下降系统 Emergency descent system	单向延伸平台 Unidirectional extension platform
充电保护系统 Charge protection system	自动坑洞保护 Automatic pothole protection	



型号 Model no.		SJPT0407	SJPT0607
1	最大工作高度 Max. working height	6m	8m
2	A最大平台高度 Max. platform height	4m	6m
3	B最小平台高度 Min. platform height	990mm	1070mm
4	C工作平台长度 Work platform length	1400mm	1400mm
5	D工作平台宽度 Work platform width	760mm	760mm
6	平台延伸尺寸 Platform extension size	600mm	600mm
7	E整机高度(护栏升起) Whole machine height(Fence expansion)	1970mm	2150mm
8	整机高度(护栏折叠) Whole machine height(Fence folded)	1600mm	1780mm
9	F整机长度 Whole machine length	1520mm	1520mm
10	G整机宽度 Whole machine width	760mm	760mm
11	额定载荷 Rated load	230kg	230kg
12	延伸平台安全工作载荷 Extended platform safe working load	100kg	100kg
13	最大工作人数 Max. workers	2	2
14	行驶速度(收藏状态) Driving speed(folded mode)	4Km/h	4Km/h
15	行驶速度(起升状态) Driving speed(lifting)	0.45Km/h	0.45Km/h
16	起升电机 Lifting motor	24V/2.2KW/2.6CC	24V/2.2KW/2.6CC
17	驱动电机 Driving motor	24V/2×0.5KW	24V/2×0.5KW
18	上升/下降时间 Lifting/falling time	28/35s	36/37s
19	最大爬坡能力 Max. climbing capacity	25%(14°)	25%(14°)
20	最大工作角度 Max. operating angle	1.5° / 2.5°	1.5° / 2.5°
21	驱动/制动 Drive/brake	双后轮 dual rear-wheels	双后轮 dual rear-wheels
22	行走方式 Driving mode	无痕橡胶轮胎 traceless rubber	无痕橡胶轮胎 traceless rubber
23	车轮规格 Wheel size	Φ305×100mm	Φ305×100mm
24	蓄电池 Storage battery	2×12V100Ah	2×12V100Ah
25	充电器 Battery charger	24V15A	24V15A
26	整机重量 Whole machine weight	830kg	994kg

