



# 轮式液驱剪叉平台

Wheeled hydraulic drive scissor platform

## SJPT1212

- 整车平顺性优化，性能优越。  
The vehicle's ride performance is superior.
- 全高度行走，配置多重安全保护装置，安全性高。  
Full height walking, equipped with multiple safety protection devices, high safety.
- 两侧整体旋出式托盘，维修方便，日常检查及维护保养便捷。  
Both sides swing-type tray is convenient for service and daily maintenance.
- 屏显人机交互，参数设置、故障诊断，参数读写，系统监控。  
Screen display man-machine interaction, parameter setting, fault diagnosis, parameter reading and writing, system monitoring.
- 电气与液压设计优化匹配，循环次数高，提供持久续航能力。  
Electrical and hydraulic design optimization match, high number of cycles, to provide lasting endurance.
- 零部件通用和模块化设计，耐用可靠。  
Parts universal and modular design, durable and reliable.



### 产品配置

#### Machine Parameters

动作蜂鸣 Action buzzer	全行程行走 Full travel	自动刹车系统 ABS
折叠围栏 Folding fence	工作时间表 Working hours table	紧急停止按钮 Emergency button
免维护电池 Maintenance-free battery	工作频闪灯 Working strobe light	故障诊断系统 Fault diagnosis system
安全检修支撑 Safety maintenance support	平台自锁门 Self-locking door	倾斜保护系统 Tilt protection system
标准运输叉车孔 Standard transport forklift hole	紧急下降系统 Emergency descent system	单向延伸平台 Unidirectional extension platform
充电保护系统 Charge protection system	自动坑洞保护 Automatic pothole protection	





型号Model no.	SJPT0812	SJPT1012	SJPT1212
1 最大工作高度 Max. working height	10m	12m	14m
2 A最大平台高度 Max. platform height	8m	9.8m	11.6m
3 B最小平台高度 Min. platform height	1210mm	1330mm	1450mm
4 C工作平台长度 Work platform length	2270mm	2270mm	2270mm
5 D工作平台宽度 Work platform width	1120mm	1120mm	1120mm
6 平台延伸尺寸 Platform extension size	900mm	900mm	900mm
7 E整机高度(护栏升起) Whole machine height(Fence expansion)	2300mm	2420mm	2540mm
8 整机高度(护栏折叠) Whole machine height(Fence folded)	1760mm	1880mm	2000mm
9 F整机长度 Whole machine length	2490mm	2490mm	2490mm
10 G整机宽度 Whole machine width	1150mm	1150mm	1150mm
11 额定载荷 Rated load	350kg	350kg	350kg
12 延伸平台安全工作载荷 Extended platform safe	113kg	113kg	113kg
13 最大工作人数 Max. workers	3	3	3
14 行驶速度(收藏状态) Driving speed(folding mode)	3.5Km/h	3.5Km/h	3.5Km/h
15 行驶速度(起升状态) Driving speed(lifting)	0.45Km/h	0.45Km/h	0.45Km/h
16 起升电机 Lifting motor	24V/4.5KW/4.5CC	24V/4.5KW/4.5CC	24V/4.5KW/4.5CC
17 驱动电机 Driving motor	24V/4.5KW	24V/4.5KW	24V/4.5KW
18 上升/下降时间 Lifting/falling time	31/35s	60/40s	62/42s
19 最大爬坡能力 Max. climbing capacity	25%(14°)	25%(14°)	25%(14°)
20 最大工作角度 Max. operating angle	1.5° / 3°	1.5° / 3°	1.5° / 3°
21 驱动/制动 Drive/brake	双前轮 dual front-wheels	双前轮 dual front-wheels	双前轮 dual front-wheels
22 行走方式 Driving mode	无痕橡胶轮胎 traceless rubber	无痕橡胶轮胎 traceless rubber	无痕橡胶轮胎 traceless rubber
23 车轮规格 Wheel size	Φ381×127mm	Φ381×127mm	Φ381×127mm
24 蓄电池 Storage battery	4×12V/120Ah	4×12V/120Ah	4×12V/120Ah
25 充电器 Battery charger	24V/30A	24V/30A	24V/30A
26 整机重量 Whole machine weight	2150kg	2600kg	2900kg

